



Adjustable Differential Feed

is easily controlled and adjusted by a dial located on the exterior, left hand side of the machine.



Automatic Lower Looper Threading



allows for easy threading in seconds— simply push the automatic threader up and then thread goes through automatically.

Adjustable Lower Knife



adjusts the lower knife quickly to change the width of fabric in the seam allowance, for perfect seams and rolled edges.

Adjustable Stitch Length



turn dial is located on the exterior right hand side within the range of 1 to 4 mm.

Standard Specifications

| Sewing Speed | 1,300 spm |
|-------------------------|--|
| Number of Threads | 3/4 Threads |
| Needle | ELX705 |
| Standard Overlock Width | Left Needle: 6mm Right Needle: 4mm Rolled Hem: 2mm |
| Stitch Length | 1-4mm(Standard: 2.5mm) |
| Differential Feed | 0.8-2.0 Ratio |
| Built-in Rolled Hemming | Right Needle/3 Thread |
| Decorative Flatlock | Right or Left Needle/3 Threads |
| Presser Foot Lift | max 6mm |
| Dimensions | 292mm(w)×295mm(d)×290mm(h) |
| Weight | 7.4kg |

Automatic Rolled Hemming

can now be created quickly and easily with built-in fingertip control. There is no need to change the foot or plate.



Overlock





Retractable Upper Knife



removes the upper knife so that threading is made safer and easier.

Lay-in Type Thread Tension Slots



throughout the machine make threading easy and efficient.

Sewing Light



Waste Collector



Optional Attachments

Blind Stitch Foot Part No. 40131946



Elasticator Foot Part No. 40131947



Beading Foot Part No. 40131949




Piping Foot Part No. 40131950



Gathering Foot Part No. 40131948



Taping Foot Part No. 40131951





JUKI CENTRAL EUROPE Sp. z o.o. ul. Poleczki 21, 02-822 Warsaw, Poland Tel.: +48 22 545 04 00 / Fax: +48 22 545 04 11